

LUBING

BREEDER DRINKER

THE STANDARD IN BREEDER DRINKERS



RELENTLESS QUALITY. EXCEPTIONAL SERVICE.

BREEDER PULLETS

FeatherSoft™ nipple with or without LitterGard cup



Number of Birds per Nipple

10-12 - FeatherSoft Nipple

12-15 - FeatherSoft Hi-Flow Nipple with LitterGard

Nipples per 10' Section - Standard

8 - 12 nipples per 10' (3 m) Section

Max. Recommended System Length

250' (80 m) per Regulator

Water Pressure Requirement - 250' Length

Pressure Regulator: min. 20 psi (1.380 bars)
max. 45 psi (3.103 bars)

Ball Tank Regulator: min. 20 psi (1.380 bars)
max. 45 psi (3.103 bars)

BREEDER PRODUCTION

LUBING 4071 breeder nipple with LitterGard cup



Number of Birds per Nipple

10-12: Breeder Nipple with LitterGard

8-10: Breeder Nipple with LitterGard for Males

Nipples per 10' Section - Standard

10 nipples per 10' (3 m) Section

12 nipples per 10' (3 m) Section

15 nipples per 10' (3 m) Section

Max. Recommended System Length

250' (80 m) per Regulator

Water Pressure Requirement - 250' Length

Pressure Regulator: min. 20 psi
max. 45 psi

WATERING SECTIONS INCLUDE:

- 10' (3 m) long, square, PVC, pipe
- Nipples with or without LitterGard
- Expansion coupler with stainless steel crimping rings
- 10' (3 m) aluminum support rail
- 4 plastic holding clips
- Galvanized connectors, 4 nuts and bolts
- 5 Hangers

DOUBLE WIRE HANGER

The double wire hanger is available for drinkers used without the electro-charger.

Double Wire Hanger

Standard Shocker Wire Hanger



NOTE: Watering sections are shipped completely pre-assembled. Only galvanized connectors and hangers are not assembled. Ten complete sections are packed in one carton. Cartons are protected, carefully banded and shipped on skids.

